Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/US2004/030024

International filing date: 13 September 2004 (13.09.2004)

Document type: Certified copy of priority document

Document details: Country/Office: US

Number: 60/588,878


Filing date: 16 July 2004 (16.07.2004)

Date of receipt at the International Bureau: 14 March 2007 (14.03.2007)

Remark: Priority document submitted or transmitted to the International Bureau in

compliance with Rule 17.1(a) or (b)





TO AND TO WITCH THE SERVED SERVED SERVED. COMES

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

March 06, 2007

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE.

APPLICATION NUMBER: 60/588,878

FILING DATE: *July 16, 2004*

RELATED PCT APPLICATION NUMBER: PCT/US04/30024

THE COUNTRY CODE AND NUMBER OF YOUR PRIORITY APPLICATION, TO BE USED FOR FILING ABROAD UNDER THE PARIS CONVENTION, IS *US60/588,878*

Certified by

Under Secretary of Commerce for Intellectual Property and Director of the United States Patent and Trademark Office PTO/SB/16 (10-01)
Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

			FOR PATENT under 37 CFR 1.53(c).	7
Express Mail Label No. ED 129135608 US				
INVENTOR(S)				
Given Name	(first and middle [if any])	Family Name or Surname	Residence (City and either State or Foreign	n Country)
appres	- C	Fett	EXCORDIDE MNS	
Blan		Taylor	Memphio, TN 38119	
Yong		Song	Eden Praire, MN	<u>55344</u>
Additional inventors are being named on the separately numbered sheets attached hereto				
TITLE OF THE INVENTION (500 characters max)				
Hip Interposition Arthroplasty				
Direct all corres		CORRESPONDENCE ADDRES	ss /	
Custome	r Number		Place Customer Number Bar Code Label here	
OR Type Customer Number here				
Individual Name advanced Bio Surfaces, INC.				
Address 5909 Baker Road				
Address Stute 550				
City		etonka State Mi		H(D)
Country Country Telephone 952-912-5400 Fax 952-912-54(0) ENCLOSED APPLICATION PARTS (check all that apply)				
Specification Number of Pages 3 CD(s), Number				
Drawing(s) Number of Sheets Other (specify) Refunn Part Cand				
Application Data Sheet. See 37 CFR 1.76				
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT				
Applicant claims small entity status. See 37 CFR 1.27. A check or money order is enclosed to cover the filing fees FILING FEE AMOUNT (\$)				
A check or money order is enclosed to cover the filing fees The Commissioner is hereby authorized to charge filing				
fees or credit any overpayment to Deposit Account Number: Payment by credit card. Form PTO-2038 is attached.				
The invention was made by an agency of the United States Government or under a contract with an agency of the				
United States Government. No.				
Yes, the name of the U.S. Government agency and the Government contract number are:				
A				
Respectfully submitted, // Date July 11/04				
SIGNATURE SIGNATURE REGISTRATION NO.				
TYPED or PRINTED NAME TEFFREY C. FELT (if appropriate) Docket Number: 32355.12.36				
TELEPHONE 952-979-1800				

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C. 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Washington, D.C. 20231.



Introduction to Hip Patent


The normal hip functions through a wide range of motion and supports loads several times the body weight in the activities of daily living. Articular cartilage on both surfaces of the hip joint aids in absorbing impact, distributing load, maintaining alignment and minimizing friction. In patients with osteoarthritis, the articular cartilage is thinned or completely eliminated and these four attributes are lost. The result for the patient with this condition is pain that may become disabling. The current treatment for painful osteoarthritis of the hip that is unresponsive to medical therapy is total hip replacement. This procedure involves removal of the femoral head and the insertion of a metal stem into the shaft of the femur. The stem is usually capped with a Morris Taper junction metallic ball. On the acetabular side of the joint, a metal cup lined with Ultra High Molecular Weight Polyethelene (UHMWPE) is inserted into the pelvic bone. The cup and stem are usually affixed with a Polymethyl Methacrolate (PMMA) grout or may have a bone in-growth fixation.

A less invasive, non-bone cutting procedure employing an implant that restores the functions of articular cartilage would be an important alternative for patients with severe osteoarthritis of the hip.

Claims

- 1. A polymeric interpositional arthroplasty positioned in the acetabulum to provide a wear and load bearing surface in an arthritic hip joint.
- 2. An implant as described in claim 1 that can be placed by minimally invasive surgical techniques or with a larger exposure.
- 3. An implant as described in claim 1 wherein the polymeric material is a biomaterial of between 55A and 100D durometer including but not limited to PEEK, polyurethane, polyethylene, etc.
- 4. An implant as described in claim 1 wherein the polymer is one of several polyurethanes described by previous ABS patent numbers 6,140,452 and 6,652,587.
- 5. A polymeric interpositional hip arthroplasty wherein the implant is composed of one or more than one durometer polyurethane or other polymeric biomaterial.
- 6. An implant as in claim 5 wherein the device has the configuration resembling the acetabulum to fit between the acetabulum and the femoral head.
- 7. An implant as in claim 6 where the device has an opening or depression to accommodate the ligament of the head of the femur.
- 8. An implant as in claim 7 wherein the major load bearing area of the device is composed of a high durometer, wear resistant polyurethane and the remaining half is composed of a softer durometer, more compliant polyurethane. In an alternative embodiment, a single durometer material may be used.
- 9. An implant as in claim 8 wherein the compliant portion of the device allows the implant to be folded for insertion through a minimally invasive surgical incision. (See drawings.)
- 10. An implant as described in claim 9 that would allow insertion through a small (i.e., 4 cm) incision following arthroscopic preparation of the joint.
- 11. An implant as described in claim 10 wherein the device is shaped to be congruent with the major anatomical features of the acetabulum.
- 12. An implant as described in Claim 11 wherein the device has a series of anchors (1-5) of barbed polyurethane to insert into predrilled holes and press-fit into the acetabulum.

- 13. An implant as described in claim 11 wherein the softer durometer material portion has an enlargement on the acetabular surface that fits into the fovea and provides added rotational stability to the implant.
- 14. An implant as described in claim 12 wherein the device has tabs or fabric around the rim to provide for suture fixation or tissue in-growth to enhance stability.
- 15. In the preferred embodiment, the implant as in claim 12 may be inserted and deployed with or without dislocating the hip. An external distracter to get enough joint space may be used.
- 16. An implant as described in claim 10 wherein the device is supplied in multiple sizes.
- 17. An insertion tool that allows placement of the implant through a mini-incision. (See drawing.)
- 18. A deployment tool that allows the surgeon to unfold the implant and seat it in the acetabulum. (See drawing.)
- 19. A set of instruments, supplied as a set with or without the implant, that allows the surgeon to prepare the acetabulum and femoral head through the arthroscopic portals or the mini-incision for placement of the acetabular implant. (See drawings.)
- 20. In an alternative embodiment the implant will cover the femoral head with the harder modulus on the superior weight bearing surface and the softer more elastomeric material around the junction with the femoral neck. (See drawing.)
- 21. An implant as in claim 19 wherein an opening is present to accommodate the ligament of the femoral head.
- 22. An implant as in claim 19 wherein the device is of a single durometer material.
- 23. An implant as in claims 19 & 21 wherein there are a series (1-5) of barbed anchors that may be press-fit into predrilled holes in the femoral head.



BEST AVAILABLE COPY